



■ 适用范围:

适用于船舶、石油开采平台、化工及爆炸性气体环境中危险区域 1 区、2 区，可燃性气体、蒸汽级别为 II A、II B、II C 级，温度组别为 T1 ~ T6 的危险场所作照明用。

■ 产品特性:

- 1、壳体用优质铜材铸造成型，灯体采用的密封结构，具有良好的防水性能和防腐性能。
- 2、采用管型荧光灯光源，安装方式为吊挂式，更换灯管方便。
- 3、电缆外径 $\varnothing 11 \sim \varnothing 12$ mm。

■ 产品认证:

- 1、经国家灯具质量监督检验中心和国家级照明灯具防爆安全监督检验站检验合格。
- 2、通过中国船级社和法国船级社型式认可。

■ The scope of application:

Applied to illumination for ship, oil exploit platform, chemical and explosive gas atmospheres zone 1, zone 2, flammable gases, vapors level II A, II B, II C level, Temperature class T1 ~ T6 dangerous places.

■ Products feature:

1. The shell adopts high quality cast brass, the light body adopts seal structure, has good waterproof performance and anti-corrosion performance.
2. Adopt tubular fluorescent light source, mounting type is hanging, it is convenient to replace the fluorescent tube.
3. Cable outside diameter is $\varnothing 11 \sim \varnothing 12$ mm.

■ Products certification:

1. This lamp has been inspected and certified by China National Lighting Fitting Quality Supervision Testing center and National Supervision and Examination Center for Explosion protected and Safety of Luminaire (NECESL).
2. Approved by type approval of CCS (China Classification Society) and type approval of BV (France Classification Society).

型号 Type	CFY20-2/1	CFY30-2/1	CFY40-2/1
L(mm)	776	1082	1385
L1(mm)	561	867	1170
防爆标志 Explosion proof mark	Ex d II CT6Gb		
防爆合格证编号 Explosion proof quality certificate number	NLE12.0553X		
电压 Voltage	220V/50Hz 220V/60Hz 110V/60Hz		
功率 Power	20WX2/1	30WX2/1	40WX2/1
灯座 Lamp holder	G13		
防护等级 Protection class	IP56		
重量 Weight(Kg)	13.0	15.1	17.3